



Application:	GK69-0903, Additive for the application of Salcomix 2K Acrylic or PUR Topcoats by brush or roll.
Properties:	Needs to be mixed with hardener SC29-0823 for brush application.
Remarks:	RFU product dries very fast on the surface. You should therefore use the product for larger areas only in exceptional cases!
Special Remarks:	It cannot be ruled out that this product contains particles < 0.1 µm The products are suitable for professional use only.

	Paint system	GK69-0903 Brush and Roll Additive			
			Salcomix Topcoats		
	Mixing ratio		2K Primer Filler, Topcoat (ACR or PUR)		
	Hardener		acc. to data sheet of corresponding product		
	Thinner		5 % by weight		
	Viscosity at 23°C DIN 4		Film Thickness (DFT)	Potlife 20°C	Gloss at 60°
	Application				
	Brush & Roll	<p>Plane and smooth surfaces: High quality Paint Roller made of foam with a fine pored surface, rounded down or dished (concave) on both ends to minimize formation of stripes and edges.</p> <p>Uneven surfaces: flocked or hairy (velours) foam paint roller are more suitable for uneven areas (more flexible).</p>			
	Drying at Object Temp.	dust-dry	Touch Dry	Ready for Assembling	Recoatable
	20°C	-	-	> 12 h	-
	60°C	-	-	45 min	-