

SATIN MATT BLACK

Advanced Paint System:

Technologically advanced acrylic formulation for durability and flexibility. Suitable for application to both metal and many plastic surfaces.

Super Coverage:

High solids formulation gives enhanced coverage allowing for fast turnaround.

'Factory' Match Standard:

Quality of finish gives professional O.E. standard

Ideal Guide Coat:

An ideal 'guide coat' for paintshop use.

Directions for Use:

Preparation: Prepare surfaces by lightly sanding with wet or dry paper. Ensure that surfaces are clean, dry and free from dirt, oil, wax etc.

CAUTION: Pressurised container; protect from sunlight. Do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray onto naked flame or any incandescent material.

Application:

Shake can vigorously for 2 minutes after the agitator ball is heard moving. Spray from a distance of 10-12" (25-30cm). Apply a light mist (key) coat, leave for 20 seconds, then apply a full cross coat. Allow 10 minutes before any further coats. Leave for 24 hours to harden.

AFTER USE Invert can and spray until valve is cleared.

Typical Specification :

| | |
|--------------|--|
| Composition | : A blend of acrylic resins, pigments, wetting agents, solvents and propellant in aerosol form |
| Appearance | : Black Paint |
| Odour | : Ketone Solvent |
| F.P. | : -40°C |
| Can Pressure | : 2.75 Bar |
| Shelf Life | : 2 years at ambient temperature. |
| Packaging | : 450ml cans. |

CODE: 433