

FACTORY WHEEL SILVER

Advanced Paint System:

Technologically advanced acrylic formulation for durability and flexibility. Suitable for application to both metal and many plastic surfaces.

Super Coverage:

High solids formulation gives enhanced coverage allowing for a fast and truly professional standard of finish.

'Factory' Match:

Specially developed to give an original factory finish.

NOTE Initial application brightness of this professional high solids wheel silver is a natural feature of the finish. The toned down final OE colour becomes apparent when fully dry.

Directions for Use:

Preparation: Prepare surfaces by lightly sanding with wet or dry paper. Ensure that surfaces are clean, dry and free from dirt, oil, wax etc.

CAUTION: Pressurised container; protect from sunlight. Do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray onto naked flame or any incandescent material.

Application:

Shake can vigorously for 2 minutes after the agitator balls are heard moving. Spray from a distance of 10-12" (25-30cm). Apply a light mist coat, leave for 20 seconds, then apply a full cross coat. Allow 10 minutes before any further coats. Leave for 24 hours to harden.

AFTER USE Invert can and spray until valve is cleared.

Typical Specification :

Composition	: A blend of acrylic resins, pigments, wetting agents, solvents and propellant in aerosol form
Appearance	: Silver Paint
Odour	: Ketone Solvent
F.P.	: -40°C
Can Pressure	: 2.75 Bar
Shelf Life	: 2 years at ambient temperature.
Packaging	: 450ml cans.

Factory Wheel Silver is just one of a range of Wheel Silvers manufactured to give a professional choice of colour.

CODE: 434